

Connecting the Gallagher TSi2 to Te Pari Dosing Gun APP

(NOTE: For Android only via Bluetooth)

Firstly, to connect the TSi to the Android device you will need a Bluetooth dongle (G03203) which will plug into an available serial Port on the TSi indicator.

Once BT Dongle plugged into TSi go to Options

- > Connect Equipment
- > Select the Serial Port the BT dongle is Plugged into ie PORT 1 (not Bluetooth Port)
- > Change
- > Data Logger
- > Show Settings
- > Baud Rate = 9600 (Note Tsi is 19200 by default and BT Dongle is 9600 by default)
- > Handshaking = None (Tsi is Hardware by default)
- > Options Send On Weight Lock
- > Select OK
- > Back (To Yard Screen)

See correct settings below:





NEW ZEALAND:

PO BOX 25, 9 ENDEAVOUR CRESCENT, OAMARU 9400. Ph: + 64 3 433 0077 Em: sales.nz@tepari.com FREEPHONE 0800 837 274 AUSTRALIA: 44 RICKY WAY, EPPING 3076 VICTORIA. Fx: 1800 669 205 Em: sales.au@tepari.com FREEPHONE 1800 650 682 USA:

14250 JUDICIAL ROAD, BURNSVILLE, MN 55306, USA. Em: sales.usa@tepari.com FREEPHONE 800 315 0433



On the Android device Go to Bluetooth Settings

- > Search for Available devices
- > Select ' RS232 Dongle ' > Enter Pin ' 0000 ' (ie 4 number zeroes)
- > Download and Install Te Pari Dosing Gun App from App Store.

Open App > Go to Settings > Change Scale Brand to 'Gallagher '

← Settings
Date Format DD/MM/YYYY
Units Metric
Scale Brand Gallagher
Enable Sound Yes



NEW ZEALAND:

PO BOX 25, 9 ENDEAVOUR CRESCENT, OAMARU 9400. Ph: + 64 3 433 0077 Em: sales.nz@tepari.com FREEPHONE 0800 837 274 AUSTRALIA: 44 RICKY WAY, EPPING 3076 VICTORIA. Fx: 1800 669 205 Em: sales.au@tepari.com FREEPHONE 1800 650 682 USA: 14250 JUDICIAL ROAD, BURNSVILLE, MN 55306, USA. Em: sales.usa@tepari.com FREEPHONE 800 315 0433



In the App Go to New Session

> Enter Required Fields * (i.e. Session name and Dosage Rate mls & KGs)

> Select Save & Start > Select Connect Weigh Scale > Connect > Locate RS232 Dongle from the list and Select it, NOTE at this point the Blue light should now be activated on the BT Dongle.

	Drench Gun Connecting
	Weigh Scale Connect
Connect Device App is not connecting to the diverch solved the scale, please connect is	EID Reader Connect
SKP GOWECT	APP SETTINGS CLOSE
← Bluetooth Device	
Select a device to connect	
Bluestick_S377 00:12:F3:24:83:6E	
GGL HR3 00:02:72:E3:81:A2	
RS232 Dongle 5C:F3:70:91:23:12	
Connecting	
Weigh Scale RS232 Dongle	Blue Light Activated on BT Dongle
EID Reader Connect	
APP SETTINGS CLOSE	L



NEW ZEALAND:

PO BOX 25, 9 ENDEAVOUR CRESCENT, OAMARU 9400. Ph: + 64 3 433 0077 Em: sales.nz@tepari.com FREEPHONE 0800 837 274 AUSTRALIA: 44 RICKY WAY, EPPING 3076 VICTORIA. Fx: 1800 669 205 Em: sales.au@tepari.com FREEPHONE 1800 650 682 USA: 14250 JUDICIAL ROAD, BURNSVILLE, MN 55306, USA. Em: sales.usa@tepari.com FREEPHONE 800 315 0433



At this point you can connect to the Drench Gun which uses Wi-Fi, please follow manufacturer's instructions for this.

On the TSi do the following;

- > Loadbars plugged in
- > Options > Create a New Session > Full Animal ID
- > Scan a Tag (assuming EID reader is connected to TSi)
- > Lock in a Weight
- > On the APP the Locked weight will appear screen and Dose to apply.





NEW ZEALAND:

PO BOX 25, 9 ENDEAVOUR CRESCENT, OAMARU 9400. Ph: +64 3 433 0077 Em: sales.nz@tepari.com FREEPHONE 0800 837 274 AUSTRALIA: 44 RICKY WAY, EPPING 3076 VICTORIA. Fx: 1800 669 205 Em: sales.au@tepari.com FREEPHONE 1800 650 682 USA: 14250 JUDICIAL ROAD, BURNSVILLE, MN 55306, USA. Em: sales.usa@tepari.com FREEPHONE 800 315 0433